

CV60

Vehicle Mount Computer



- Choice of leading Microsoft® Windows® CE .NET and XP/XPe operating systems
- Brilliant 12.1" (30.73cm) TFT touch screen display with direct sunlight viewing option
- Powerful Intel™ P-III Ultra Low Power 800 MHz processor
- Bluetooth™ accessory support
- Cisco Compatible 802.11b/g radio with industry standard wireless security protocols
- Integrated Bluetooth wireless scanner support
- Extreme temperature option
- Versatile ADC Control Center that enables real-time decision-making through integration and management of multiple types of data inputs

Continuing Intermec's legacy reputation of developing reliable terminals, the CV60 computer excels in the most adverse environments with full PC functionality. The CV60 terminal, either fixed or vehicle mounted, puts wireless supply chain management right where the data is—at the dock, on the warehouse floor, in the trailer or in the yard—for the toughest material handling applications.

The CV60 offers choices of either wired or wireless accessories. By integrating Bluetooth™ technology in the CV60, the user has fewer accessories to install, cables to contend with and tethered wires to get in the way. This eliminates costly cable replacement and improves user satisfaction and supports Intermec's Bluetooth line of printers and hand held bar code scanners.

The modular design allows for the convenient swap-out of hard drives. By integrating dual-diversity antennas, mounting of the CV60 is streamlined. This industry-leading design also provides seamless network connectivity within the Enterprise. This saves time, lowers the cost of overall ownership and permits on-site personnel to upgrade hardware quickly and efficiently.

In addition, a brilliant 12.1" (30.73cm) high resolution TFT SVGA color display simplifies user interaction with touch-screen capabilities and

color graphics. A day-light readable display option is also available to allow easier viewing in direct sunlight.

With a choice of hard drive technologies, the CV60 excels in vehicle-mount environments. A uniquely designed vibration and shock dampening solution is offered for rotating drive applications, as well as an industrial grade solid state solution for the most demanding environments including freezing temperatures. The system can also avoid inadvertent shutdowns and power loss, common to material handling vehicles, with an uninterruptible power supply (UPS).

The cast magnesium housing of the CV60 received an IP65 seal rating. With a heated display option and chemically hardened glass that is 50% thicker than industry standard, the CV60 can withstand harsh environments where dust, moisture or extreme temperatures are a constant. To further protect your investment, the integration of a Gore™ vent prevents internal condensation from occurring at extreme temperatures.

State-of-the-art, industry-standard development tools, such as Microsoft's .NET Compact Framework, Visual C++™, Visual Basic™, Java® and HTML™ can be used with CV60. The CV60 will also accommodate thin, thick or browser-based applications.

With the addition of Intermecc's SmartSystems™, the CV60 can be used to remotely manage peripherals such as Bluetooth scanners and RFID, as well as to remotely and easily manage global deployments.

Physical Description

With a cast magnesium housing, the CV60 is a rugged computer designed for real time data collection applications, using either a vehicle or stationary mount, in manufacturing, warehousing, distribution, and transportation environments.

Physical Characteristics

Height: 27.1cm (10.67")

Width: 34cm (13.4")

Depth: 9.5cm (3.7")

Weight: 5 kg (11 lbs.)

Environmental

Standard Operating Temperature:

-20° to 50° C (-4° to 122° F) – Solid State

0° to 50° C (32° to 122° F) – Rotating

Extreme Operating Temperature:

-30° to 50° C (-22° to 122° F) – Solid State HDD (With heated display option)

Storage Temperature:

-30° to 70° C (-22° to 158° F)

Humidity: 5 % to 95 % RH Non-condensing

Shock and Vibration Protection: Withstands standard material handling vehicle environments. Meets or Exceeds MIL STD 810F

Rain and Dust Resistance: Sealed to IP65 (Dust tight and jetted water)

Standard Features

Power: Choice of two external DC/DC converters 6-60V DC input for 12-60V systems (gas truck)
15-96 VDC input DC/DC for 60-96V systems (electrical truck)

AC/DC Converter

Uninterruptible Power Supply option for unstable power sources

Hardware

Memory: 256MB SDRAM standard; expandable to 512MB; 512KB Flash

Microprocessor: Intel P-III Ultra Low Power 800MHz embedded processor

Display: Brilliant 12.1" Color TFT 800 x 600 SVGA; 100 degree viewing angle;

300 NIT; with Heated Option. Sunlight readable (non-heated) option also available

User Interface: High resolution, resistive touch panel (field replaceable)

Operating Systems

Windows CE .NET 4.2

Windows XP Professional Edition

Windows XP Embedded

Hard Drive Options

Solid State drive options for rugged, vehicle / freezer based applications

Shock/Vibration dampening rotating drive option for stationary, standard temperature and select mobile applications

Network Connectivity

10BaseT/100BaseT Ethernet

Application Connectivity

Supports Terminal Emulation (TE 2000) applications. Supports standard application environments including Win32 Microsoft Foundation Classes (MFC), Microsoft .NET Framework and Microsoft .NET Compact

Cisco Compatible Extensions

Version 2 Supported

LEAP

CKIP

VLAN

Integrated Radio Options

Wireless LAN

Data Rates: Up to 54 Mbps per IEEE 802.11g

Standards Compliant:

IEEE 802.11g - 2.4 GHz

IEEE 802.11b (2.4 GHz - DSSS)

Radio Power: 100mW typical

Security: WEP, WPA2, 802.1x (EAP-TLS, TTLS, LEAP, PEAP)

Certifications: Wi-Fi, WPA2, Cisco Certified

Compliance: FCC Part 15, CE mark

Wireless PAN

Integrated Bluetooth™ compatible module

Antenna Options

Integrated diversity antenna options for LAN, Bluetooth and bar code scanner.

Remote patch LAN antenna

Data Collection Scanner Support

Tethered serial bar code scanner

Tethered RFID scanner

Integrated Bluetooth radio for wireless accessory support

Interfaces

(2) Standard Serial Ports – DB9

(2) USB Host ports v1.1

(1) PS/2 Keyboard Port

(1) Locking Power Input

On / Off Switch

Audio 3.5mm stereo jack

Microphone In / Mono Output (VoIP ready) 2.5mm jack

Internal Speaker / Beeper

Accessible Expansion Slots

One 6.4cm (2.5") IDE drive bay

One Solid State type II card Bus slot

*Bluetooth™ is a trademark owned by the Bluetooth SIG, Inc., USA.

Display Backlighting Contains Mercury, Dispose of Properly.



North America

Corporate Headquarters

6001 36th Avenue West
Everett, Washington 98203
Phone: (425) 348-2600
Fax: (425) 355-9551

South America & Mexico

Headquarters Office

Newport Beach, California
Phone: (949) 955-0785
Fax: (949) 756-8782

Europe/Middle East &

Africa Headquarters Office

Reading, United Kingdom
Phone: +44 118 923 0800
Fax: +44 118 923 0801

Asia Pacific

Headquarters Office

Singapore
Phone: +65 6303 2100
Fax: +65 6303 2199

Internet

www.intermec.com
Worldwide Locations:
www.intermec.com/locations

Sales

Toll Free NA: (800) 934-3163
Toll in NA: (425) 348-2726
Freephone ROW: 00 800 4488 8844
Toll ROW: +44 134 435 0296

OEM Sales

Phone: (425) 348-2762

Media Sales

Phone: (513) 874-5882

Customer Service and Support

Toll Free NA: (800) 755-5505
Toll in NA: (425) 356-1799



Copyright © 2007 Intermecc Technologies Corporation. All rights reserved. Intermecc is a registered trademark of Intermecc Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611406-01F 09/07

In a continuing effort to improve our products, Intermecc Technologies Corporation reserves the right to change specifications and features without prior notice.



Email: sales@milestechinc.com

Phone: 800-783-2132

1150 Heather Drive • Lake Zurich, IL 60047