

# PC41

## Desktop Printer



- Compact desktop printer for applications where space is limited
- Unique double clam shell design offers easy drop-in loading of paper and ribbon supplies
- Serial and Centronics parallel interfaces are standard
- Battery option facilitates mobility
- Optional ethernet, IBM Twinax or Coax interfaces
- QuickMount™ printhead
- Free printhead replacement program

Intermec's PC41 printer facilitates label printing in almost any environment including retail, office, healthcare, logistics, government, manufacturing, and warehouse – particularly where space is limited. The PC41 is a small, compact desktop printer that prints labels, tickets, and tags up to 4.1 inches wide to meet compliance mandates.

The unique double clam shell design minimizes down time with quick and easy media replenishment and QuickMount™ printhead changes. Labels and ribbons are easily swapped out via drop-in replacement. Additionally, Intermec offers a free printhead replacement program for customers who utilize Intermec printer supplies with the bar code label printer.

Flexible communication options enable users to utilize open ports without interfering with equipment that may already be connected to the computer.

The PC41 comes standard with RS-232 Serial and Centronics parallel interfaces. Optional interfaces include external ethernet or IBM Twinax or Coax interfaces.

The battery option for the PC41 facilitates mobile printing. Labels are printed quickly and easily throughout a full shift, whether the printer is powered via AC outlet or battery.

The PC41 printer is backwards compatible with existing 7421 printer installations. These small desktop label printers utilize Intermec's unique programming language (IPL).

Bar code label printing has never been so easy. The PC41 facilitates getting started with choice of stationary or mobile printing, and quick and easy media replenishment in a small compact printer designed to fit where space is limited.

#### Application

Direct Thermal or Direct Thermal/Thermal Transfer label, ticket, and tag printer.

#### Physical Characteristics

**Length:** 257 mm (10.11 in)  
**Height:** 167 mm (6.58 in)  
**Width:** 230 mm (9.06 in)  
**Weight:** 2.3 kg (5.07 lbs)

#### Print Specifications

**Max Print Width:** 108 mm (4.25")

#### Print Speed

Selectable 2, 3, and 4 ips (50.8, 76.2, and 101.6 mm/sec)

#### Print Resolution

8 dots/mm (203 dpi)

#### Label/Ticket/Tag

**Max Width:** 118 mm (4.65 in)  
**Min. Width:** 25 mm (1 in)  
**Thickness (includes liner):** 0.06 mm (0.003 in) to 0.15 mm (0.006 in)  
Optional thick media spring for media up to 0.20 mm (0.008 in)  
**Style:** Roll-fed, die-cut, continuous or fanfold labels, tags or tickets  
**Label roll max diameter:** 127 mm (5 in)  
**Label roll core ID (min/max):** 25.4 mm (1 in)/38.1 mm (1.5 in)  
**Media type:** A wide selection of stock and custom size labels are available.

#### Ribbon Roll

**Ribbon roll max diameter:** 41 mm (1.6 in)  
**Ribbon roll core inner diameter:** 13 mm (0.5 in) with notches  
**Ribbon type:** Wax, wax/resin, resin

#### Interface

**Standard:** RS-232 Serial and Centronics Parallel  
**Optional:** External Ethernet, IBM Twinax or Coax

#### Software

LabelShop® START label design software Interdriver™ for Microsoft Windows™ supports: Windows™ 98/Me/2000 and 32-bit and 64-bit editions of XP Professional™, Server 2003™ and Vista™

#### Bar Code Symbologies

**1-D:** Code 11, Code 39, Extended Code 39, Code 93, Extended Code 93, Code 128 UCC, Code 128, Codabar, Interleaved 2 of 5 UPC-A, UPC-E, 2 and 5 digit add-on, UPC Shipping container code, EAN-13, EAN-8, 2 and 5 digit add-on, EAN-128, Postnet  
**2-D:** Code One, Code 16K, Code 49, DataMatrix, MaxiCode, PDF417, QR Code

#### Fonts

Supports 21 resident bitmap, 3 resident scalable fonts, and users can download up to 16 bitmap fonts using PrintSet™.

#### Character Sets

**Resident codepages:** Code page 850, French, German, ISO 256 character, Italian, Norwegian/Danish, Spanish, Swedish/Finnish, Swiss, UK ASCII, USA ASCII.

#### Memory

**Standard:** 512 kB RAM  
**Optional:** 1 MB Flash

#### Protocol

IPL (Intermec Programming Language)

#### Power Supply

**Separate power supply unit -**  
**Input:** 100-240V AC/50-60 Hz, 1.9A  
**Output:** 24 V DC, 3.0 A

#### Operating Environment

**Operating temperature:** 5°C to 40°C (40°F to 104°F)  
**Storage temperature:** -20°C to 60°C (-4°F to 140°F)  
**Humidity:** 10% to 90% non-condensing

#### Regulatory Approvals

FCC 47 CFR part 15A, CE, UL + cUL, GS, NOM, C-Tic

#### Options

Cutter, 1 MB Flash Memory Cartridge, External Ethernet Adapter, Mobile battery unit, IBM Twinax or Coax Interfaces

#### North America

**Corporate Headquarters**  
6001 36th Avenue West  
Everett, Washington 98203  
Phone: (425) 348-2600  
Fax: (425) 355-9551

#### South America & Mexico

**Headquarters Office**  
Rua Samuel Morse,  
120-9º, Andar  
Brooklin - 04576-060  
São Paulo/SP - BRAZIL  
Phone: +55 11 5502.6770  
Fax: +55 11 5502.6780  
www.intermec.com.br

#### Europe/Middle East &

**Africa Headquarters Office**  
Reading, United Kingdom  
Phone: +44 118 923 0800  
Fax: +44 118 923 0801

#### Asia Pacific

Headquarters Office  
Singapore  
Phone: +65 6303 2100  
Fax: +65 6303 2199

#### Internet

www.intermec.com  
Worldwide Locations:  
www.intermec.com/locations

#### Sales

Toll Free NA: (800) 934-3163  
Toll in NA: (425) 348-2726  
Freephone ROW: 00 800 4488 8844  
Toll ROW: +44 134 435 0296

#### OEM Sales

Phone: (425) 348-2762

#### Media Sales

Phone: (513) 874-5882

#### Customer Service and Support

Toll Free NA: (800) 755-5505  
Toll in NA: (425) 356-1799

Copyright © 2009 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611586-01D 02/09

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.



**Email:** sales@milestechinc.com  
**Phone:** 800-783-2132  
1150 Heather Drive • Lake Zurich, IL 60047